



































ENGINE

TYPE

DISPLACEMENT (CC) MAX POWER (PS @ RPM) MAX TORQUE (NM @ RPM) CLUTCH GEARBOX

TRIPLE SPARK 4-VALVE DTS-i ENGINE, CLOSED FUEL INJECTION LIQUID COOLED

373.3 35 @ 8000 35 @ 6500 **ASSIST & SLIPPER CLUTCH** 6 SPEED

CHASSIS & SUSPENSION

FRAME REAR SUSPENSION

BEAM TYPE PERIMETER FRAME FRONT SUSPENSION TELESCOPIC 43MM FORKS MULTI STEP ADJUSTABLE MONO SHOCK

BRAKES & TYRES

TYRES FRONT TYRES REAR

BRAKES FRONT (MM) TWIN CHANNEL ABS, 320 DIA DISC BRAKES REAR (MM) TWIN CHANNEL ABS, 230 DIA DISC 110/70-17 RADIAL 150/60-17 RADIAL

ELECTRICALS

BATTERY

12V, BAH VRLA **HEADLAMP** FULL LED WITH AUTO HEADLAMP ON (AHO)

DIMENSIONS

LXWXH(MM) 2156 X 813 X 1112 WHEELBASE (MM) 1453 **GROUND CLEARANCE (MM)** KERB WEIGHT (KG) **FUEL CAPACITY (LTR)** 13



page-33 page-34



